



**LA GAMMA** | THE RANGE, LA GAMME  
MODELL ÜBERSICHT, LA GAMA



| Modello<br>Model<br>Modèle<br>Modell<br>Modelo | Peso<br>Weight<br>Poids<br>Betriebsgewicht<br>Peso | Motore<br>Engine<br>Moteur<br>Motor<br>Motor | Potenza motore<br>Engine power<br>Type moteur<br>Motorleistung<br>Potencia motor | Profondità di scavo<br>Digging depth<br>Prof. d'excavation<br>Grabtiefe<br>Prof. de excavación | Larghezza max.<br>Max. width<br>Largeur max.<br>Max. breite<br>Anchura max. |
|------------------------------------------------|----------------------------------------------------|----------------------------------------------|----------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|
| <b>12ZT</b>                                    | 1.160 kg (2.557 lb)                                | KUBOTA STAGE 5<br>- TIER 4 FINAL             | 10,2 kW - 13,7 HP                                                                | 1.860 mm (73,2 in)                                                                             | min. 790 mm (31,1 in)<br>max. 1.050 mm (41,3 in)                            |
| <b>14SR</b>                                    | 1.230 kg (2.712 lb)                                | KUBOTA STAGE 5<br>- TIER 4 FINAL             | 10,2 kW - 13,7 HP                                                                | 2.045 mm (80,5 in)                                                                             | min. 790 mm (31,1 in)<br>max. 1.050 mm (41,3 in)                            |
| <b>15ZT</b>                                    | 1.580 kg (3.483 lb)                                | YANMAR STAGE 5<br>- TIER 4 FINAL             | 11,3 kW - 15,4 HP                                                                | 2.020 mm (79,5 in)                                                                             | min. 990 mm (39,0 in)<br>max. 1.250 mm (49,2 in)                            |
| <b>17SR</b>                                    | 1.660kg (3.660 lb)                                 | YANMAR STAGE 5<br>- TIER 4 FINAL             | 11,3 kW - 15,4 HP                                                                | 2.020 mm (79,5 in)                                                                             | min. 990 mm (39,0 in)<br>max. 1.250 mm (49,2 in)                            |
| <b>18ZT</b>                                    | 1.720 kg (3.792 lb)                                | YANMAR STAGE 5<br>- TIER 4 FINAL             | 11,3 kW - 15,4 HP                                                                | 2.280 mm (89,8 in)                                                                             | min. 990 mm (39,0 in)<br>max. 1.300 mm (51,2 in)                            |
| <b>19ZT</b>                                    | 1.770 kg (3.902 lb)                                | YANMAR STAGE 5<br>- TIER 4 FINAL             | 13,7 kW - 18,6 HP                                                                | 2.280 mm (89,8 in)                                                                             | min. 990 mm (39,0 in)<br>max. 1.300 mm (51,2 in)                            |
| <b>19TR</b>                                    | 1.900 kg (4.189 lb)                                | YANMAR STAGE 5<br>- TIER 4 FINAL             | 13,7 kW - 18,6 HP                                                                | 2.380 mm (93,7 in)                                                                             | min. 990 mm (39,0 in)<br>max. 1.300 mm (51,2 in)                            |
| <b>22SR</b>                                    | 2.090 kg (4.608 lb)                                | KUBOTA STAGE 5<br>- TIER 4 FINAL             | 15,4 kW - 20,9 HP                                                                | 2.560 mm (100,8 in)                                                                            | min. 990 mm (39,0 in)<br>max. 1.300 mm (51,2 in)                            |
| <b>25ZT</b>                                    | 2.540 kg (5.401 lb)                                | YANMAR STAGE 5<br>- TIER 4 FINAL             | 15,5 kW - 21,1 HP                                                                | 2.725 mm (107,2 in)                                                                            | 1.500 mm (59,1 in)                                                          |



| Modello<br>Model<br>Modèle<br>Modell<br>Modelo | Peso<br>Weight<br>Poids<br>Betriebsgewicht<br>Peso | Motore<br>Engine<br>Moteur<br>Motor<br>Motor | Potenza motore<br>Engine power<br>Type moteur<br>Motorleistung<br>Potencia motor | Profondità di scavo<br>Digging depth<br>Prof. d'excavation<br>Grabtiefe<br>Prof. de excavación | Larghezza max.<br>Max. width<br>Largeur max.<br>Max. breite<br>Anchura max. |
|------------------------------------------------|----------------------------------------------------|----------------------------------------------|----------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|
| <b>28ZT</b>                                    | 2.700 kg (5.952 lb)                                | KUBOTA STAGE 5<br>- TIER 4 FINAL             | 18,5 kW - 25,0 HP                                                                | 2.660 mm (104,7 in)                                                                            | 1.550 mm (61,0 in)                                                          |
| <b>35ZT</b>                                    | 3.350 kg (7.385 lb)                                | KUBOTA STAGE 5<br>- TIER 4 FINAL             | 18,5 kW - 25,0 HP                                                                | 2.880 mm (113,3 in)                                                                            | 1.580 mm (62,2 in)                                                          |
| <b>42ZT</b>                                    | 4.050 kg (8.929 lb)                                | KUBOTA STAGE 5 TURBO<br>- TIER 4 FINAL       | 32,3 kW - 43,9 HP                                                                | 3.085 mm (121,5 in)                                                                            | 1.750 mm (68,9 in)                                                          |
| <b>45TR</b>                                    | 4.450 kg (9.811 lb)                                | KUBOTA STAGE 5 TURBO<br>- TIER 4 FINAL       | 32,3 kW - 43,9 HP                                                                | 3.190 mm (125,6 in)                                                                            | 1.750 mm (68,9 in)                                                          |
| <b>50ZT</b>                                    | 4.650 kg (10.251 lb)                               | KUBOTA STAGE 5 TURBO<br>- TIER 4 FINAL       | 42,6 kW - 57,9 HP                                                                | 3.330 mm (131,1 in)                                                                            | 1.900 mm (74,8 in)                                                          |
| <b>55TR</b>                                    | 5.250 kg (11.574 lb)                               | KUBOTA STAGE 5 TURBO<br>- TIER 4 FINAL       | 42,6 kW - 57,9 HP                                                                | 3.460 mm (136,2 in)                                                                            | 1.900 mm (74,8 in)                                                          |
| <b>58ZT</b>                                    | 5.400 kg (11.905 lb)                               | KUBOTA STAGE 5 TURBO<br>- TIER 4 FINAL       | 45,0 kW - 61,2 HP                                                                | 3.400 mm (133,9 in)                                                                            | 1.980 mm (78,0 in)                                                          |
| <b>60ZT</b>                                    | 5.700 kg (12.566 lb)                               | KUBOTA STAGE 5 TURBO<br>- TIER 4 FINAL       | 45,0 kW - 61,2 HP                                                                | 3.850 mm (151,6 in)                                                                            | 1.980 mm (78,0 in)                                                          |
| <b>65TR</b>                                    | 6.200 kg (13.669 lb)                               | KUBOTA STAGE 5 TURBO<br>- TIER 4 FINAL       | 45,0 kW - 61,2 HP                                                                | 3.950 mm (155,5 in)                                                                            | 1.980 mm (78,0 in)                                                          |



| Modello<br>Model<br>Modèle<br>Modell<br>Modelo | Peso<br>Weight<br>Poids<br>Betriebsgewicht<br>Peso | Motore<br>Engine<br>Moteur<br>Motor<br>Motor | Potenza motore<br>Engine power<br>Type moteur<br>Motorleistung<br>Potencia motor | Profondità di scavo<br>Digging depth<br>Prof. d'excavation<br>Grabtiefe<br>Prof. de excavación | Larghezza max.<br>Max. width<br>Largeur max.<br>Max. breite<br>Anchura max. |
|------------------------------------------------|----------------------------------------------------|----------------------------------------------|----------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|
| <b>85SB</b>                                    | 8.300 kg (18.298 lb)                               | YANMAR STAGE 5 TURBO<br>-TIER 4 FINAL        | 53,7 kW - 73,0 HP                                                                | 3.800 mm (149,6 in)                                                                            | 2.320 mm (91,3 in)                                                          |
| <b>90ZT</b>                                    | 9.000 kg (19.825 lb)                               | YANMAR STAGE 5 TURBO<br>-TIER 4 FINAL        | 53,7 kW - 73,0 HP                                                                | 4.270 mm (168,1 in)                                                                            | 2.320 mm (91,3 in)                                                          |
| <b>95UR</b>                                    | 9.100 kg (20.062 lb)                               | YANMAR STAGE 5 TURBO<br>-TIER 4 FINAL        | 53,7 kW - 73,0 HP                                                                | 4.220 mm (166,1 in)                                                                            | 2.320 mm (91,3 in)                                                          |
| <b>100TR</b>                                   | 9.900 kg (21.825 lb)                               | YANMAR STAGE 5 TURBO<br>-TIER 4 FINAL        | 53,7 kW - 73,0 HP                                                                | 4.570 mm (179,9 in)                                                                            | 2.320 mm (91,3 in)                                                          |



PALE COMPATTE GOMMATE

COMPACT WHEELED LOADERS, CHARGEUSES SUR PNEUS,  
REIFENKOMPAKTLADER, MINICARGADORAS COMPACTAS DE RUEDAS



| Modello<br>Model<br>Modèle<br>Modell<br>Modelo | Peso<br>Weight<br>Poids<br>Betriebsgewicht<br>Peso | Motore<br>Engine<br>Moteur<br>Motor<br>Motor | Potenza motore<br>Engine power<br>Type moteur<br>Motorleistung<br>Potencia motor | Carico operativo<br>Operating load<br>Charge opérationnel<br>Betriebshublast<br>Carga operativa | Larghezza max.<br>Max. width<br>Largeur max.<br>Max. breite<br>Anchura max. |
|------------------------------------------------|----------------------------------------------------|----------------------------------------------|----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|
| 17SK                                           | 3.600 kg (6.834 lb)                                | KUBOTA STAGE 5 TURBO<br>-TIER 4 FINAL        | 50,0 kW - 67,1 HP                                                                | 980 kg (2.161 lb)                                                                               | 1.715 mm ( 67,5 in)                                                         |
| 19SK                                           | 4.350 kg (8.598 lb)                                | KUBOTA STAGE 5 TURBO<br>-TIER 4 FINAL        | 53,7 kW - 73,0 HP                                                                | 1.450 kg (3.638 lb)                                                                             | 1.840 mm (72,4 in)                                                          |



PALE COMPATTE CINGOLATE

COMPACT TRACKED LOADERS, CHARGEUSES SUR CHENILLES,  
RAUPENKOMPAKTLADER, MINICARGADORAS COMPACTAS DE CADENAS



| Modello<br>Model<br>Modèle<br>Modell<br>Modelo | Peso<br>Weight<br>Poids<br>Betriebsgewicht<br>Peso | Motore<br>Engine<br>Moteur<br>Motor<br>Motor | Potenza motore<br>Engine power<br>Type moteur<br>Motorleistung<br>Potencia motor | Carico operativo<br>Operating load<br>Charge opérationnel<br>Betriebshublast<br>Carga operativa | Larghezza max.<br>Max. width<br>Largeur max.<br>Max. breite<br>Anchura max. |
|------------------------------------------------|----------------------------------------------------|----------------------------------------------|----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|
| 18TL                                           | 4.300 kg (9.039 lb)                                | KUBOTA STAGE 5 TURBO<br>-TIER 4 FINAL        | 50,0 kW - 67,1 HP                                                                | 1.640 kg (3.616 lb)                                                                             | 1.790 mm (70,5 in)                                                          |
| 20TL                                           | 5.470 kg (12.059 lb)                               | KUBOTA STAGE 5 TURBO<br>-TIER 4 FINAL        | 53,7 kW - 73,0 HP                                                                | 2.572 kg (5.670 lb)                                                                             | 2.090 mm (82,3 in)                                                          |





| Modello<br>Model<br>Modèle<br>Modell<br>Modelo | Peso<br>Weight<br>Poids<br>Betriebsgewicht<br>Peso | Motore<br>Engine<br>Moteur<br>Motor<br>Motor | Potenza motore<br>Engine power<br>Type moteur<br>Motorleistung<br>Potencia motor | Larghezza max.<br>Max. width<br>Largeur max.<br>Max. breite<br>Anchura max. |
|------------------------------------------------|----------------------------------------------------|----------------------------------------------|----------------------------------------------------------------------------------|-----------------------------------------------------------------------------|
| ESP22                                          | 1.910 kg (4.211 lb)                                | KUBOTA STAGE 5<br>- TIER 4 FINAL             | 15,4 kW - 20,9 HP                                                                | min. 990 mm (39,0 in)<br>max. 1.300 mm (51,2 in)                            |
| ESP25                                          | 2.400 kg (5.291 lb)                                | YANMAR STAGE 5<br>- TIER 4 FINAL             | 15,5 kW - 21,1 HP                                                                | 1.500 mm (59,1 in)                                                          |
| ESP28                                          | 2.800 kg (6.173 lb)                                | KUBOTA STAGE 5<br>- TIER 4 FINAL             | 18,2 kW - 24,7 HP                                                                | 1.550 mm (61,0 in)                                                          |
| ESP35                                          | 3.050 kg (6.764 lb)                                | KUBOTA STAGE 5<br>- TIER 4 FINAL             | 18,2 kW - 24,7 HP                                                                | 1.580 mm (62,2 in)                                                          |
| ESP45                                          | 4.200 kg (9.259 lb)                                | KUBOTA STAGE 5 TURBO<br>- TIER 4 FINAL       | 32,3 kW - 43,3 HP                                                                | 1.750 mm (68,9 in)                                                          |
| ESP55                                          | 4.800 kg (10.582 lb)                               | KUBOTA STAGE 5 TURBO<br>- TIER 4 FINAL       | 43,3 kW - 57,1 HP                                                                | 1.900 mm (74,8 in)                                                          |
| ESP58                                          | 5.300 kg (11.685 lb)                               | KUBOTA STAGE 5 TURBO<br>- TIER 4 FINAL       | 45,0 kW - 61,2 HP                                                                | 1.980 mm (78,0 in)                                                          |
| ESP65                                          | 5.400 kg (11.904 lb)                               | KUBOTA STAGE 5 TURBO<br>- TIER 4 FINAL       | 45,0 kW - 61,2 HP                                                                | 1.980 mm (78,0 in)                                                          |



| Modello<br>Model<br>Modèle<br>Modell<br>Modelo | Peso<br>Weight<br>Poids<br>Betriebsgewicht<br>Peso | Motore<br>Engine<br>Moteur<br>Motor<br>Motor | Potenza motore<br>Engine power<br>Type moteur<br>Motorleistung<br>Potencia motor | Larghezza max.<br>Max. width<br>Largeur max.<br>Max. breite<br>Anchura max.         |
|------------------------------------------------|----------------------------------------------------|----------------------------------------------|----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| <b>ESP100ZT4</b>                               | 8.840 kg (19.489 lb)<br>• 10.220 kg (22.531 lb)    | YANMAR STAGE 5 TURBO<br>-TIER 4 FINAL        | 53,7 kW - 73,0 HP                                                                | STD: 2.320 mm (91,3 in)<br>OPT: min. 2.320 mm (91,3 in)<br>max. 2.920 mm (115,0 in) |
| <b>ESP100UR4</b>                               | 8.340 kg (18.387 lb)<br>• 9.720 kg (21.429 lb)     | YANMAR STAGE 5 TURBO<br>-TIER 4 FINAL        | 53,7 kW - 73,0 HP                                                                | STD: 2320 mm (91,3 in)<br>OPT: min. 2.320 mm (91,3 in)<br>max. 2.920 mm (115,0 in)  |

• carro variabile - variable undercarriage - chassis variable - verstellb. unterwagen - carro inferior variable

# EUROCOMACH **GEOSERVICE**



**MACHINE SETTINGS**



**DETAILED REPORTS**



**GEOFENCE CREATION**





**SMS/EMAIL NOTIFICATION**



**CURFEW SETTING**



**MOVEMENT ALARM (ENGINE OFF)**



**ANOMALIES ALARMS**



**MACHINE GEOLOCATION**

Thanks to the GEO-SERVICE's intuitive interface, machines are always safe and under control.



Attachments

*Increase **your** productivity*



For more information about the new line of customized Eurocomach equipment, contact your sales representative.

This image shows a blank sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.



**COMPANY WITH  
QUALITY SYSTEM  
CERTIFIED BY DNV GL  
= ISO 9001 =**

LAST UPDATE: 01/07/2022

*Sampierana S.p.A. reserves the right to change technical data and product characteristics at any time without prior notice. The photos are for illustrative purposes only and do not necessarily refer to standard products.*