

## DEMOLITION HAMMERS

CNH hammers are of the "one-piece" type, i.e. built in a single piece and without tie-rods. This feature makes them resistant to work on even the toughest construction sites and less maintenance by the operator is required. Products with the best high-alloy steels and the best heat treatment techniques guarantee reliability and durability. The range consists of 8 models for excavators with operating weights from 0.8 to 11 tonnes.



Model	MDE 70Plus	MDE 100 H	MDE 150 H	MDE 200 H	MDE 250 H	MDE 300 H	MDE 400 H	MDE 500 H
Excavator (tonne)	0.8-1.4	1.5-2.2	2.3-3.0	2.8-4.5	4.0-7.0		6.0-9.5	9.6-11.0
Weight (Kg)	70	100	145	190	250	320	430	540
Energy (J)	280	400	580	750	950	1200	1700	2300
Frequency (c/min)	800/1750	800/2300	800/2000	900/1900	850/1800	600/1500	500/1300	600/1200
Oil flow rate (l/min)	18-23	20-30	22-40	25-55	30-60	50-70	65-90	70-95
Pressure (bar)	100	110	110	130	140	160	150	150
Height (mm)	583	666	666	869	869	904	1135	1135
∅ tool (mm)	40	45	48	55	65	75	80	90
Back pressure (bar)	30	30	30	30	30	30	30	30
Hydraulic hoses (inches)	2 - 1/2"	2 - 1/2"	2 - 1/2"	2 - 1/2"	2 - 1/2"	2 - 3/4"	2 - 3/4"	2 - 3/4"



MOIL POINT



CHISEL TOOL



## ACCESSORIES:

### Tools:

	MDE 70 Plus	MDE 100 H	MDE 150 H	MDE 200 H	MDE 250 H	MDE 300 H	MDE 400 H	MDE 500 H
Moil point								
Chisel								

Also available on request: flat tool, pile driver tool, wood cutter and asphalt cutter.

### Pin coupler:

Model	MDE 70 Plus	MDE 100 H	MDE 150 H	MDE 200 H	MDE 250 H	MDE 300 H	MDE 400 H	MDE 500 H

### Quick-coupling attachment coupler:

Quick-coupling attachment	Excavator (tonne)							
	0.6-2.1	2.2-2.5	2.6-3.5	3.6-4.1	4.2-5.5	5.6-6.0	6.1-7.5	7.6-10.0
AR	AR 15	AR 30		AR 40		AR 50		AR 70
CR	CR 15	CR 30		CR 40		CR 50		CR 70
CS JANUS	CS 10	CS 30					CS 80	
KLAC	KLAC C	KLAC D			KLAC E			KLAC F
S NORDIC	S30/150 - S30/180		S40-200			S45	S50	
CM	CM 30				CM 100			
KLAC Alternatik	0	1		2		3		

### Connection kit:

	Excavator (tonne)							
	0.6-2.1	2.2-2.5	2.6-3.5	3.6-4.1	4.2-5.5	5.6-6.0	6.1-7.5	7.6-10.0